

## TECHNICAL DATA SHEET

# POLYPROPYLENE

## PP H30S



### Manufacturer:

SINOPEC ZHENHAI REFINING & CHEMICAL CO.  
Address: Zhenhai District, Ningbo City, Zhejiang Province  
Postcode: 315207  
Tel: +86 (574) 86440114  
Fax: +86 (574) 86270077  
Website: <http://www.zhlh.sinopec.com>  
Emergency Telephone Number: +86-13602220658

### Typical Application

PP Fiber grade is widely used in the production of bulked continuous filament (BCF), fine and superfine staple fiber, cigarette filter tow and superfine non-woven fabric in high-speed and ultrahigh-speed spinning and spunbonded non-woven fabric production. It has a variety of application in the decoration, medical sanitation, martial and clothing production sectors.

### Package, Storage and Transportation

The resin is packaged in 25kg/bag without palletizing. The resin should be stored in a drafty, dry warehouse and away from fire and direct sunlight. It should not be piled up in the open air. During transportation, the resin should not be exposed to strong sunlight or rain and should not be transported together with sand, soil, scrap metal, coal or glass. Transportation together with toxic, corrosive and flammable substance is strictly prohibited.

### Typical Data

Test Item	Test Method	Spec.	Unit
Cleanliness	SH/T1541	≤5	Pc/kg
MFR	GB/T3682	37± 7.0	g/ 10min
Powder Ash	GB/T9345.1	≤0.030	%
Tensile Yield Strength	GB/T1040.2	≥30.0	Mpa
Isotacticity Index	GB/T2412	≥96.0	%